


4NKT 06 Range Expanded and New 4NHT Insert Type Released



KEY POINT

TaeguTec has introduced two new additions to the CHASE2MILL product line -- 4NKT 06 several corner R expansion and the 4NHT 06-ML/AL ground insert types.

The **4NKT 06** insert type corner R range has been expanded (04R-20R) to meet the wider range of corner R requirements demanded by today's industries. This simplifies the response needed for specific corner R inserts required by products in a variety of industries such as automotive, aerospace and mold and die.

Further additions to the **CHASE2MILL** line include the **4NHT 06-ML** characterized by a low cutting load and excellent surface roughness due to the insert's ground cutting edges that minimize built-up-edges. One further expansion to the line includes the **4NHT 06-AL** uncoated inserts for aluminum and non-ferrous cutting applications to further widen the cutting tool solution range of the **CHASE2MILL** family of products.


Features


- 4NKT 0603□□R range expanded: 04R-20R
- 4NHT 06-ML: Improved cutting load, excellent surface roughness and minimized built-up-edges
- 4NHT 06-AL: Uncoated inserts for aluminum and non-ferrous material machining



4NK(H)T 06

Insert





4NHT

Size	Dimension (mm)								
	IC	S	APMX	BS	RE				
06	6.6	4.2-5.0	5.8-6.2	0.6-1.0	0.4-2.0				





			1		1				
Insert		Designation	Recommended machining conditions		Coated				Uncoated
		Boolghation	Feed (mm/tooth)	ap (mm)	TT9080	TT8080	TT6080	TT2510	K10
	4NKT	060304R-M new	0.07-0.15	0.5-5.0	•				
		060308R-M	0.07-0.15	1.0-5.0	•	•	•	•	
		060312R-M new	0.07-0.15	1.0-5.0	•				
		060316R-M	0.07-0.15	2.0-4.5	•	•		0	
		060320R-M (new)	0.07-0.15	2.0-4.5	•				
	4NKT	060304R-ML new	0.05-0.10	0.5-5.0		•			
		060308R-ML	0.05-0.10	1.0-5.0	•	•			
		060312R-ML new	0.05-0.10	1.0-5.0		•			
		060316R-ML	0.05-0.10	2.0-4.5	•	•			
		0603 <mark>20R-ML new</mark>	0.05-0.12	2.0-4.5	•	•			
	4NHT	060304R-ML new	0.05-0.13	0.5-5.0	•				
		060308R-ML new	0.05-0.13	1.0-5.0	•	•			
6	4NHT	060304R-AL (new)	0.1-0.40	1.0-5.0					•
		060308R-AL (new)	0.1-0.40	1.0-5.0					•
•									

• : Standard items

 \bigcirc : Semi standard items



